



MANNOL Energy Formula JP 5W-30 7914

Innovative, energy-saving ester-containing fully synthetic premium engine oil for modern gasoline engines. Designed in accordance with the requirements of American, Japanese and Korean automakers specifically for engines with direct injection systems (GDI, D4, NEO-DI, CGI DISI, I-CDTI), turbocharged.

Product properties:

- High fuel efficiency due to reduced viscosity and optimal anti-friction properties;
- Highly effective additive package and synthetic base provide confident cold start in any conditions, thereby significantly reducing engine starting wear;
- Due to its excellent washing and dispersing properties and the highest thermal oxidative stability, it effectively fights against all types of deposits and keeps engine parts clean throughout the entire interval between replacements;
- The presence of ester components in combination with optimal viscosity-temperature characteristics guarantees the highest strength of the oil film, which provides excellent anti-wear properties which, combined with excellent pumpability, significantly increase engine life even in the most severe operating conditions;
- Compatible with the latest exhaust gas aftertreatment systems;
- A special synthetic base optimizes the operation of engines with direct injection systems, with turbocharging, as well as with various mechanisms for changing the valve timing (VTEC, i-VTEC, VTE-i, VTE-i, CVT, VWL, MIVEC, AVCS (AVLS), CVTCS and others.);
- It is used in engines with extended oil change intervals (Long Life) and conventional;
- Meets or exceeds the requirements of 'API SP' industry standard, helping address LSPI (Low Speed Pre-Ignition) and making it a preferred choice for modern direct injection turbocharged gasoline engines.

Designed for multi-valve gasoline engines of cars, light SUVs, vans and light trucks, as well as SUV cars and light-duty vans, where the performance level API SP (RC) / ILSAC GF-6A of this viscosity class is required.

Recommended for cars: ACURA, INFINITI, LEXUS, NISSAN, MITSUBISHI, SUZUKI, TOYOTA, HONDA, SUBARU, HYUNDAI, KIA.

The oil is not suitable for use in heavy trucks and similar vehicles!

Specifications

SAE 5W-30

Recommendation

API SP (RC)

ILSAC GF-6A

GM dexos 1 Gen3

FORD WSS-M2C929-A

FORD WSS-M2C946-A

FORD WSS-M2C946-B1

FORD WSS-M2C961-A1

FIAT 9.55535-CR1

HONDA HTO-06

GM 6094M

CHRYSLER MS-6395

CHRYSLER MS-13340

VWC 53034

LEXUS

MAZDA

SUZUKI

SSANGYONG

TOYOTA

NISSAN

PACKAGING

4L	MN7914-4	Plastic	4 pcs/box
1000L	MN7914-IBC	Pallet tank	
	MN7914-DR		
60L	MN7914-60	Drum	
20L	MN7914-20	Plastic	
7L	MN7914-7		
	MN7914-5		
1L	MN7914-1	Plastic	20 pcs/box